
pyreaper Documentation

Release 0.0.9

Ryuichi YAMAMOTO

Feb 12, 2023

Contents

1 Installation guide	3
2 API	5
2.1 pyreaper.reaper	5
3 Indices and tables	7
Python Module Index	9
Index	11

A python wrapper for REAPER (Robust Epoch And Pitch EstimatoR).

<https://github.com/r9y9/pyreaper>

CHAPTER 1

Installation guide

The latest release is available on pypi. You can install it by:

```
pip install pyreaper
```

Note that you have to install numpy to build C-extensions.

If you want the latest development version, assuming you have cython installed, run:

```
pip install git+https://github.com/r9y9/pyreaper
```

or:

```
git clone https://github.com/r9y9/pyreaper
cd pyreaper
git submodule update --init --recursive
python setup.py develop # or install
```

This should resolve the package dependencies and install pyreaper properly.

CHAPTER 2

API

<code>pyreaper.reaper(x, fs[, minf0, maxf0, ...])</code>	REAPER (Robust Epoch And Pitch EstimatoR)
--	---

2.1 pyreaper.reaper

`pyreaper.reaper` (*x, fs, minf0=40.0, maxf0=500.0, do_high_pass=True, do_hilbert_transform=False, inter_pulse=0.01, frame_period=0.005, unvoiced_cost=0.9*)
REAPER (Robust Epoch And Pitch EstimatoR)

Perform REAPER analysis given an audio signal

Parameters

x [np.ndarray, dtype=np.int16] Input audio signal

fs [int] Sampling frequency

minf0 [float] Min f0. Default is 40.0.

maxf0 [float] Max f0. Default is 500.0.

do_high_pass [Bool] Enable Rumble-removel highpass filter. Default is True.

do_hilbert_transform [Bool] Enable Hilbert transform that may reduce phase distortion. Default is False.

inter_pulse [float] Regular inter-mark interval to use in UV pitchmark regions. Default is 0.01 (sec)

frame_period [float] Frame period. Default is 0.005 (sec).

unvoiced_cost [float] Set the cost for unvoiced segments. Default is 0.9, the higher the value the more f0 estimates in noise.

Returns

pm_times [np.ndarray, dtype=np.float32] Pitch mark time series in seconds

pm [np.ndarray, dtype=np.int32] Pitch mark. Value 1 and 0 means voiced frame and unvoiced frame, respectively.

f0_times [np.ndarray, dtype=np.float32] F0 time series in seconds

f0 [np.ndarray, dtype=np.float32] F0 contour

corr [np.ndarray, dtype=np.float32] Correlations

Raises

RuntimeError

- if EpochTracker Init failed
- if EpochTracker ComputeFeatures failed
- if EpochTracker TrackEpochs failed
- if EpochTracker ResampleAndReturnResults failed

Examples

```
>>> from scipy.io import wavfile
>>> import pysptk
>>> import pyreaper
>>> fs, x = wavfile.read(pysptk.util.example_audio_file())
>>> pm_times, pm, f0_times, f0, corr = pyreaper.reaper(x, fs)
```

CHAPTER 3

Indices and tables

- genindex
- search

Python Module Index

p

pyreaper, ??

Index

P

`pyreaper` (*module*), 1

R

`reaper()` (*in module pyreaper*), 5